

ZMD405AT/CT, ZFD405AT/CT, ZMD410AT/CT, ZFD410AT/CT

E650 Series 3

Technical Data



Building on its tradition of industrial meters, Landis+Gyr has developed the E650 Series 3, the latest generation of ZxD400 meters. These meters feature a new hardware platform, combining modern technology with proven functions.

Date: 30.01.2014

File name: D000030106 E650 ZxD400xT Series 3 Technical Data en p.docx

Revision history

Version	Date	Comments
e	27.01.2011	Updated document template and type designation table entry "045x 4 outputs, additional power supply 100-240 VAC/VDC"
g	15.10.2012	Introduction text extended and summary of main features inserted. Temperature range operation expanded from –40 °C to +70 °C. Immunity conducted disturbances specified. New extension board 326x. ADP1 adapter replaced with ADP2 adapter. Minor formatting and typing error corrections. Index synchronized with German version.
p	30.01.2014	Added extension board 047x.

Although the information contained within this document are presented in good faith and believed to be correct, Landis+Gyr (including its affiliates, agents and employees) disclaim any and all liability for any errors, inaccuracies or incompleteness relating to the product. Landis+Gyr makes no warranty, representation or guarantee regarding the performance, quality, durability or suitability of the products for any particular purpose. To the fullest extent permitted by law Landis+Gyr disclaims (1) any and all liability arising out of the use of the product, (2) any and all liability, including, but without limitation to, special, consequential and indirect damages and losses, and (3) any and all implied warranties, including, but without limitation to, fitness for purpose and merchantability.

The information contained in this document is strictly confidential and is intended for the addressee only. The unauthorised use, disclosure, copying, alteration or distribution of this document or the contents thereof is strictly prohibited and may be unlawful.

All product information are subject to change without notice.

Design

E650 is the most proven platform for industrial and commercial meters with more than 1.5 million meters installed in over 70 countries.

E650 is the result of a century Landis+Gyr experience in metering field combined with high quality requirements.

Range

E650 meters are the answer to a wide range of specific needs: from the reliable commercial meter to the complex measuring device with comprehensive additional functionality for sophisticated data acquisition and flexible tariff control at large industrial customers.

Application

E650 offers high flexibility to connect to different power system distributions from low up to high voltage levels thanks to various voltage and current settings.

Covering most of the energy measurement and calculation use cases, E650 meters record active and reactive energy consumption in all three-phase four-wire and three-phase three-wire networks with powerful recording capabilities.

For instance, 32 energy rate registers can be combined in many different ways through 17 measured quantities, per quadrants or per phases. Those registers can be controlled by various sources (Control inputs, time switch or communication signals). 24 max demand rate registers and 2 lowest power factor registers with time stamp are available as well.

8 operating time registers settable with various control signals could be used in various situations from fraud tentatives up to operation follow up.

All registers can be stored in stored value profiles that allows the storage of 84 values for one year with a weekly reset.

One out of 2 load profiles available can be used to record energy registers, last average demand, average power factor for billing purposes in the case of dynamic tariffs, for instance, with an integration period programmable according to real needs.

E650 has various options to detect fraud attempts from energy calculation modes up to hardware options as DC – strong field detection or integrated terminal cover detection switch with time stamped records in the event logbook and optional local signalisation over a special LED or arrows on the LCD display.

In the Time of Use part the utility can define up to 12 different week/season tables, 100 special days and 12 day tables that are controlled by 16 time switch control signals. Programmable passive tables and emergency settings allow to manage unexpected or future situations without any additional workload.

A comprehensive logbook offers the possibility to record more than 70 different events with time stamp in a circular table of 500 events.

E650 can be used for network monitoring with key average measurement RMS recordings (U, I, P, Q, PF, THD).

Up to 26 channels can be recorded in a second load profile with a different integration period programmable from 1 minute up to 60 minutes which allows an excellent network monitoring.

Most power quality events (over-/ under-voltages, power failures) are logged in dedicated event logs with number of event, timestamp, duration, magnitude and phase allowing an easy calculation of SAIDI (System Average Interruption Duration Index) parameters. Up to 30 events can be recorded for over-/under-voltages and power failures each.

All information (stored data profile, load profiles, logbook, dedicated event log) are stored in non-volatile memory, which prevents any losses of critical data information.

Through a control table, it is possible to combine various signal sources to control signals with Boolean operators.

E650 is able to achieve simple automatism without any additional components.

Such control capabilities could be used not only to control registers but outputs locally or remotely as well.

E650 have extended digitals input and outputs (static and relays) from 3 inputs/2 outputs as basis combined with a variety of option boards offering different capabilities.

Modular communication

AT/CT-type S650 SGT are equipped with modular communication units which provide the right choice for the best data channel at all times. "Plug&Play" modules also offer you full freedom of choice for deployment of new communication technologies.

Installation support

An indication of phase voltages, phase angles, rotating field and energy direction supports the installation.

Summary of the main features

	ZMD400	ZFD400
Measured quantities		
Energy (quadrants, ph, direction, reverse stop)		17 ¹⁾
Summation channels (virtual or digital input)		2 ¹⁾
Losses (OLA, NLA)		2 ¹⁾
Losses (I^2 , U^2)		2 ¹⁾
Active energy harmonic distortion		2 ¹⁾
Rotating field direction		•
Energy and demand registers		
Energy rates		32
Total energy		27
Demand rates		24
Power factor (combimeters only)		2
Last average and current demand		2x10
Memory depth per value (84 values selectable)		53
Other registers		
Operating time		8
Diagnostic registers		41
Tariff module		
Season tables		12
Week tables		12
Day tables		12
Special days (set 26 years ahead)		100
Time of use control signals		16
Emergency settings		•
Active/passive time tables		•
Control table – 7 different control sources combinations to control 16 control signals		
Communication and digital inputs, TOU; Voltage & PF, demand, current monitoring; Status, missing voltages		•
Load profiles (integration period from 1 up to 60 minutes)		
Independent load profiles		2 (1 optional)
Maximum number of captured channels		26
Data information storage (stored data profile, 2 load profiles, event log, dedicated event logs)		
Non-volatile memory (Flash memory)		•

¹⁾ Value recordable in dedicated load profile from 1 up to 60 minutes (typical 15 minutes).

	ZMD400	ZFD400
Instantaneous values		
Voltage phase-neutral or phase-ground	● ²⁾	–
Voltage phase-phase	–	● ²⁾ (U1-2, U2-3 only)
Current	(I1, I2, I3, IN) ²⁾	(I1, I3) ²⁾
Frequency	● ²⁾	● ²⁾
Phase angles	● ²⁾	–
Active power (+/-)	(P1, P2, P3, P total) ²⁾	P total ²⁾
Reactive power (+/-)	(Q1, Q2, Q3, Q total) ²⁾	Q total ²⁾
Power factor	PF1, 2, 3, (PF total) ¹⁾	PF total ²⁾
THD of phases current/voltage (absolute)	(Phase 1, 2, 3) ²⁾	(Phase 1, 3) ²⁾
THD of phases current/voltage (percent)	Sum ²⁾	Sum ²⁾
THD of active energy (import/export)	Sum ²⁾	Sum ²⁾
Measurements monitoring with thresholds and records in event log		
Over-/under-voltage phase-neutral	●	–
Over-/under-voltage phase-phase	–	●
Over-current (phase and neutral)	●	●
Event logs		
Maximum number of entries time stamped (s)	500	
Dedicated event log with snapshot		
Maximum number of entries time stamped (s)	3x30	
Primary or secondary values	●	
SMS alarm capabilities		
Alarm numbers of digital inputs	1 max.	
Alarms on event (SMS)	●	

¹⁾ Value recordable in dedicated load profile from 1 up to 60 minutes (typical 15 minutes).

²⁾ Value recordable in another load profile from 1 up to 60 minutes (typical 1 minute).

E650 Series 3 ZxD400AT/CT – Technical specifications

General

Voltage

Nominal voltage U_n ZMD400xT	3 x 58/100 V to 69/120 V 3 x 110/190 V to 133/230 V 3 x 220/380 V to 240/415 V
Extended operating voltage range	3 x 58/100 to 240/415 V

Nominal Voltage U_n ZFD400xT

	3 x 100 to 120 V 3 x 220 to 240 V
Extended operating voltage range	3 x 100 to 415 V

Voltage range	80 to 115%
---------------	------------

Frequency

Nominal frequency f_n	50 or 60 Hz
Tolerance	$\pm 2\%$

IEC-specific data

Current

Nominal current I_n	1 A, 2 A, 5 A, 5 1 A
-----------------------	-----------------------

Maximal current I_{max}

Metrological 2 A, 5 A	200% I_n
Metrological 1 A	2 A, 10 A
Metrological 5 1 A	6 A
Thermal 1 A, 2 A, 5 A, 5 1 A	12 A

Short-circuit current	0.5 s with $20 \times I_{max}$
-----------------------	--------------------------------

Measurement accuracy

ZxD405xT	
Active energy, to IEC 62053-22	class 0.5 S
Reactive energy, to IEC 62053-23	accuracy 1%

ZxD410xT

Active energy, to IEC 62053-21	class 1
Reactive energy, to IEC 62053-23	accuracy 1%

Measurement behaviour

Starting current ZxD405xT	
According to IEC	0.1% I_n
Typical	0.07% I_n
5 1 A	as 1 A meter

Starting current ZxD410xT	
According to IEC	0.2% I_n
Typical	0.14% I_n
5 1 A	as 1 A meter

The start-up of the meter is controlled by the starting power and not by the starting current.

Starting power in M-circuit	single phase
Nominal voltage x starting current	

Starting power in F-circuit	all phases
Nominal voltage x starting current x $\sqrt{3}$	

MID-specific data

Current (for classes B and C)

Rated current I_n	1.0 A, 5.0 A
---------------------	--------------

Minimum current I_{min}	0.01 A, 0.05 A
---------------------------	----------------

Transitional current I_{tr}	0.05 A, 0.25 A
-------------------------------	----------------

Maximum current I_{max}	2.0 A, 10.0 A
---------------------------	---------------

Measurement accuracy	to EN 50470-3
ZxD400xT	classes B and C

Measurement behaviour

Starting current I_{st}	
Class B: I_{st}	0.002 A, 0.01 A
Class C: I_{st}	0.001 A, 0.005 A

General

Operating behaviour

Voltage failure (power-down)

Bridging time	0.5 s
Data storage	after another 0.2 s
Switch off	after approx. 2.5 s

Voltage restoration (power-up)

Function standby 3 phases	after 2 s
Function standby 1 phase	after 5 s
Detection of energy direction and phase voltage	after 2 to 3 s

Power consumption

Power consumption per phase in voltage circuit

Phase voltage	58 V	100 V	240 V
Active power (typical)	0.4 W	0.5 W	0.7 W
Apparent power (typical)	0.8 VA	1.0 VA	1.7 VA

Power consumption per phase in current circuit

Phase current	1 A	5 A	10 A
Active power (typical)	5 mW	0.125 W	0.5 W
Apparent power (typical)	5 mVA	0.125 VA	0.5 VA

Environmental influences

Temperature range	to IEC 62052-11
Operation	-40 °C to +70 °C
Storage	-40 °C to +85 °C

Temperature coefficient

Range	-40 °C to +70 °C
Average value (typical)	± 0.012% per K
at $\cos\varphi=1$ (from 0.05 I_b to I_{max})	± 0.02% per K
at $\cos\varphi=0.5$ (from 0.1 I_b to I_{max})	± 0.03% per K

Impermeability to IEC 60529	IP51
-----------------------------	------

Electromagnetic compatibility

Electrostatic discharges	to IEC 61000-4-2
Contact discharge	15 kV

Immunity conducted disturbances	2 to 150 kHz
According to CENELEC	TR 50579

Electromagnetic RF fields	to IEC 61000-4-3
80 MHz to 2 GHz	10 and 30 V/m

Radio interference suppression	
according to IEC/CISPR 22	class B

Fast transient burst test	to IEC 61000-4-4
Current and voltage circuits under load	
according to IEC 62053-21/23	4 kV
Auxiliary circuits > 40 V	2 kV

Fast transient surge test	to IEC 61000-4-5
Current and voltage circuits	4 kV
Auxiliary circuits > 40 V	1 kV

Insulation strength

Insulation strength	4 kV at 50 Hz during 1 min.
---------------------	-----------------------------

Impulse voltage 1.2/50 μ s	to IEC 62052-11
Current and voltage circuits	8 kV
Auxiliary circuits	6 kV

Protection class II	to IEC 62052-11	<input type="checkbox"/>
---------------------	-----------------	--------------------------

Calendar clock

Calendar type	Gregorian or Persian (Jalaali)
---------------	--------------------------------

Accuracy	< 5 ppm
----------	---------

Backup time (power reserve) meter

With supercapacitor	> 20 days
Charging time for max. backup time	300 h
With battery (optional)	10 years
Battery type	CR-P2

Display

Characteristics

Type	LCD liquid crystal display
Digit size in value field	8 mm
Number of digits in value field	up to 8
Digit size in index field	6 mm
Number of digits in index field	up to 8

Inputs and outputs

Control inputs	
Control voltage U_S	100 to 240 V _{AC}
Input current	< 2 mA ohmic at 230 V _{AC}

Output contacts

Type	solid-state relay
Voltage	12 to 240 V _{AC/DC}
Max. current	100 mA
Max. switching frequency (pulse length 20 ms)	25 Hz

Optical test outputs	active and reactive energy
Type	red LED
Number	2
Meter constant	selectable

Relay contacts	on extension board 326x
Type	relay
Voltage	240 V _{AC}
Max. current	8 A
Max. operations with $\cos\varphi \sim 1$	100 000 op.

Control inputs	on extension board 326x
Control voltage U_S	12 to 24 V _{DC}
Input current	< 6 mA ohmic at 24 V _{DC}

Communication interface

Optical interface	to IEC 62056-21
Type	serial, asynchronous, half-duplex
Max. transmission rate	9600 bps
Protocols	IEC 62056-21 and dlms

Communication units

Exchangeable communication units for various applications.

Additional power supply (optional)

On extension board 045x	
Nominal voltage range	100 to 240 V _{AC/DC}
Tolerance	80 to 115% U_n
Frequency	50 or 60 Hz
Max. power consumption	6.8 W

On extension board 046x and 326x	
Nominal voltage range	12 to 24 V _{DC}
Tolerance	80 to 115% U_n
Max. power consumption 046x	3.5 W
Max. power consumption 326x	5.5 W

On extension board 047x	
Nominal voltage range	12 to 60 V _{DC}
Tolerance	80 to 115% U_n
Max. power consumption	5.0 W

Weight and dimensions

Weight	approx. 1.5 kg
--------	----------------

External dimensions

Width	177 mm
Height (with short terminal cover)	244 mm
Height (with standard terminal cover)	281.5 mm
Height (with extended hook)	305.5 mm
Depth	75 mm

Suspension triangle

Height (with extended hook)	230 mm
Height (suspension eyelet open)	206 mm
Height (suspension eyelet covered)	190 mm
Width	150 mm

Terminal cover

Short	no free space
Standard (opaque, transparent)	40 mm free space
Long (opaque, transparent)	60 mm free space
GSM	60 mm free space
ZxB type 80 mm	80 mm free space
ZxB type 110 mm	110 mm free space
ADP2 adapter	

Material housing

Polycarbonate, partly glass-fibre reinforced

Environmental

RoHS compliant design


Connections

Phase connections	
Type	screw type terminals
Diameter	5.2 mm
Recommended conductor cross section	4 to 6 mm ²
Screw head	Pozidrive Combi No. 2
Screw dimensions	M4 x 8
Screw head diameter	≤ 5.8 mm
Tightening torque	< 1.7 Nm


Other connections

Type	screwless spring-type terminal
Max. current of voltage outputs	1 A
Max. voltage of inputs	250 V


Meter dimensions (standard terminal cover)




Terminal dimensions



Terminal layout according to DIN



Symmetrical terminal layout (optional, ZMD400 only)



Type designation		ZMD	4	10	C	T	44	4207	S3
Network type									
ZFD	3-phase 3-wire network (F-circuit)								
ZMD	3-phase 4-wire network (M-circuit)								
Connection type									
4	Transformer operated								
Accuracy class									
10	Active energy class 1 (IEC), B (MID)								
05	Active energy class 0.5s (IEC), C (MID)								
Measured quantities									
C	Active and reactive energy								
A	Active energy								
Construction									
T	With exchangeable communication units								
Tariffication									
21	Energy rates, external rate control via control inputs								
24	Energy rates, internal rate control via time switch (additionally possible via control inputs)								
41	Energy and demand rates, external rate control via control inputs								
44	Energy and demand rates, internal rate control via time switch (additionally possible via control inputs)								
All versions with 3 control inputs and 2 output contacts									
Additional functions									
000x	No extension board								
060x	6 outputs								
240x	2 control inputs, 4 outputs								
420x	4 control inputs, 2 outputs								
326x	3 control inputs, 2 relays outputs, auxiliary power supply 12 to 24 V _{DC}								
045x	4 outputs, auxiliary power supply 100 to 240 V _{AC} /V _{DC}								
046x	4 outputs, auxiliary power supply 12 to 24 V _{DC}								
047x	4 outputs, auxiliary power supply 12 to 60 V _{DC}								
xxx0	No additional functions								
xxx2	DC-magnet detection								
xxx7	Load profile								
xxx9	DC-magnet detection and load profile (integrated terminal cover switch option only available in this configuration)								
Series 3									

Contact:

Landis+Gyr AG

Theilerstrasse 1

CH-6301 Zug

Switzerland

Phone: +41 41 935 6000

www.landisgyr.com

Landis
| Gyr+
manage energy better