

**TABLE A – XLP Service Drop/Service Entrance**

PHASE CONDUCTOR			NEUTRAL-MESSENGER			WEIGHT PER 1000 FEET (LBS)	AMPACITY (AMPS)	PRODUCT
SIZE AWG	STRANDING	COVER THICK (MILS)	SIZE (AWG)	STRANDING	MIN. ULTIMATE STRENGTH (LBS)	VIP	VIP	Code Word
<b>DUPLEX</b>								
8	7	45	8	7	610	115.8	84	Kappa
6	7	45	6	7	959	179.1	110	Sigma
<b>TRIPLEX</b>								
8	7	45	8	7	610	180.6	84	Garamond
6	7	45	6	7	959	277.2	110	Gothic
4	7	45	4	7	1505	429.6	145	Caslon
2	7	45	4	7	1505	593.7	195	Primer
2	7	45	2	7	2360	669.7	195	Century
1/0	19	60	1/0	7	3705	1070.6	260	Corinthian
2/0	19	60	2/0	7	4765	1338.7	300	Doric
4/0	19	60	4/0	7	7479	2099.4	395	
<b>QUADRUPLEX</b>								
6	7	45	6	7	959	375.3	95	Tallahassee
4	7	45	4	7	1505	580.0	125	Richmond
2	7	45	2	7	2360	902.3	165	Seattle
1/0	19	60	1/0	7	3705	1443.1	225	Nashville
2/0	19	60	2/0	7	4765	1802.7	260	Lincoln