	VOCAB NUMBER 111042		CABLE, SINGLE CORE, BLACK, 7/0.67, 2.5 MM ² PVC INSULATED, 0.6/1 KV GRADE.			
			SPECIFICATION I	DETAILS	HO STATES	
1.	GENERAL REQU	AS ter	mperature rating of 75	°C or class as V75.	omply with AS 3147– 1992 all have minimum insulation	
	1.1 All cables shall have the characteristics for insulation under AS 3000 – Wiring rules AS3008 part 1 and 2.				AS3008 part 1 and 2.	
2.	CONDUCTOR:		Single Core - 2.5mm², 7/0.67 copper stranded			
3.	INSULATION:		PVC insulated 0.6/1 kV Grade, V75.			
4.	TESTS:					
5.	SAMPLE: PNG Power Limited may require the submission of samples for approval pto bulk production				samples for approval prior	
6.	PACKING & MARKING:		The cables shall be suitably packed in wooden drums having softwood sides and battens. The total weight shall not exceed 900kg. Drums to be AS/NZ 2857 – 1996 Timber drum or AS3983 – 1991. Wooden drums capable of storage life of 4 years under tropical conditions. Each drum shall be clearly marked with the information specified in AS/NZS 2857 or AS 3983.			
7.	PACKING LENGT) metres			
3.	STANDARD CORE COLOURS: BLACK – As per rule 3.2 of AS 3000 – 1991, SAA Wiring Rules (PNGS 1022)					
	Unit of Measure: Metre Rejection: PNG Power Ltd reserves all rights to reject whole or part of the order not complying with this specification and is not liable for any cost or loss with the return of rejects to the Supplier. Facilitation of Invoice Credit must commence between the supplier and PNG Power Ltd through the process of PNG Power Ltd					
Prawing References: N/A Manufacturer's Product Code:						
ppro	oval by Grevasius P Chair r	eni: Signature:	PARDS COMMITTEE		5,9,18	
		DAT	A REVIEW ENDORS	SEMENT		
	NAME	170	LE	SIGNATURE	DATE	
	MAIVIE				DATE	
wali	NAM .	Engineer - Standards		To a	25/09/18	