	VOCAB N	UMRER			
	111046		CABLE, SINGLE CORE, BLACK, 7/0.85, 4 MM ² PVC INSULATED, 0.6/1 KV GRADE.		
SPECIFICATION DETAILS					
1.		QUIREMENT:	insulation temperature	nder this specification shall co latest equivalent standard e rating of 75°C or class as V	l. It shall have minimum
	1.1 All cables shall have the characteristics for insulation under AS 3000 – Wiring rules AS3008 part 1 and				
2.	CONDUCTOR	:	Single Core - 4mm², 7/		,
3.	INSULATION:		PVC insulated 0.6/1 kV Grade, V75.		
4.	TESTS:		PNG Power will require the provision of test certificates giving results on tests made on the cables in accordance with the AS 1660 – 1998 or latest equivalent standard.		
5.	SAMPLE:		PNG Power Limited may require the submission of samples for approval prior to bulk production		
6.	PACKING & MARKING:		The cables shall be suitably packed in wooden drums having softwood sides and battens. The total weight shall not exceed 900kg. Drums to be AS/NZ 2857 – 1996 Timber drum or AS3983 – 1991. Wooden drums capable of storage life of 4 years under tropical conditions. Each drum shall be clearly marked with the information specified in AS/NZS 2857 or AS 3983.		
•	PACKING LENGTH:		1000 metres		
•	STANDARD CORE COLOURS: BLACK – As per rule 3.2 of AS 3000 – 1991, SAA Wiring Rules (PNGS 1022)				
	Unit of Measure: Met Rejection: PNG Power the return of rejects to Ltd Discrepancy Report	Itd reserves all sinhas as	- HEWards soon A	complying with this specification and is a ween the supplier and PNG Power Ltd th	
rawii	ng References:	N/A		anufacturer's Product Code	
		S.	TANDARDS COMMITTE		
prov	val by Grevasius Cha l	Peni: Signa Irman	ature: ###	Date: 25	5,9,18
			DATA REVIEW ENDOR	SEMENT	
	NAME		TITLE	SIGNATURE	DATE
_					PAIL
vali F	Rawali	Engineer - Star	ndards and Materials	- Sand	25/09/18